



OPTIM



Unit 6 / 29 Bay Rd
Taren Point, NSW 2229
Australia
p +61 2 8338 0555
www.optim.global
ABN 33 609 107 780

Shipping Container Specifications

CONTAINER	DOOR WIDTH	DOOR HEIGHT	INTERNAL LENGTH	INTERNAL WIDTH	INTERNAL HEIGHT	CAPACITY	TARE WEIGHT	Image (Indicative)
Standard 20'	2.340m	2.280m	5.900m	2.350m	2.393m	33.2m3	2,350kg	
Standard 40'	2.340m	2.280m	12.032m	2.350m	2.392m	67.7m3	3,780kg	
High Cube 40'	2.340m	2.590m	12.032m	2.350m	2.700m	76.3m3	3,900kg	
Reefer 20'	2.282m	2.216m	5.425m	2.270m	2.250m	28.3m3	2,950kg	
Reefer 40'	2.282m	2.155m	11.570m	2.270m	2.250m	57.8m3	4,300kg	
Reefer 40' (High Cube)	2.294m	2.530m	11.570m	2.270m	2.500m	66.6m3	4,570kg	
Open Top 20'	2.340m	2.280m	5.900m (Roof Opening L 5.30m)	2.350m (Roof Opening W 2.20m)	2.340m	32.23m3	2,500kg	
Open Top 40'	2.340m	2.280m	12.032m (Roof Opening L 11.50m)	2.350m (Roof Opening W 2.200m)	2.340m	65.5m3	3,850kg	
Flat Rack 20'			5.600m	2.400m	2.150m		2,530kg	
Flat Rack 40'			11.600m	2.200m	1.950m		5,950kg	
Platform 20'			6.058m	2.400m	2.150m		2,750kg	
Platform 40'			12.180m	2.245m	1.950m		5,950kg	

** Please note that container weights and sizes may vary from shipping line to shipping line. The above is a general guide to container sizing and weight specifications.